


Evolens

Recessed Downlight



192/228 (ES/OP) Lumens	3 Watts	6500K	Recessed Mounting
High Temperature Li-Ion Battery	Class I	IP 20	8Y Warranty

Order Code	EVLNM3/L3W*OPW
Mode of operation	Non-maintained
Input voltage	230V/240VAC 50/60Hz
Power consumption	7.9VA
Battery type	High Temperature Rechargeable Lithium-Ion 3.7V 2.6Ah
Battery discharge current @ 3.7V	0.6A
Lamp	3 Watt WHITE LED - 50000 Hr
Lamp Colour	Cool White - 6500K
Lumen level in emergency	192 lumens in Escape Route 228 lumens in Open Plan
Ingress protection	IP20
Cable entry	Recessed Pack
Cutout Size	100mm Cutout - 110mm Minimum Ceiling Void
Classification	Class I
Product Weight	0.3kg
Packaging Weight	0.05Kg
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity

Materials

Lamp Housing: Aluminium
Lamp Head: ABS

Standard Colour: *White - RAL 9016
Add **WH** to Order Code
Alternative Colours: *Black - RAL 9017
Add **BL** to Order Code

Warranty


Standard Warranty: 8 Years
Alternative Warranty: 10 Years
Add **I10Y** to Order Code

System	Order Code	Mode of Operation	Battery	Lumens (Emergency)	Dimensions (mm)		
					A	B	C
Standalone	EVLNM3/L3W*OPW	Non-Maintained	High Temperature 3.7V, 2.6Ah Li-Ion	Open Plan - 228 Escape Route - 192	105	78	110

Photometrics

Mounting Height	Lighting level directly under Luminaire (Lux)	Luminaire Spacing (Metres)											
		Escape Route				Open Plan							
		0.5lx	1.0lx	0.5lx	1.0lx	0.5lx	1.0lx	0.5lx	1.0lx	0.5lx	1.0lx	0.5lx	1.0lx
2m	14.11	6.7	5.9	15.0	13.4	10.5	8.7	6.1	4.0	2.0	1.5	3.9	10.8
2.5m	9.03	7.7	6.6	17.5	15.4	11.7	9.8	6.0	4.1	2.1	1.8	4.0	11.8
3m	6.27	8.6	7.2	19.7	17.2	12.7	10.9	5.7	4.6	2.3	1.9	4.1	12.5
4m	3.53	9.9	7.2	23.5	19.8	14.7	12.6	6.0	5.4	2.7	2.3	4.0	13.7
6m	1.57	9.5	3.4	28.8	19.0	18.2	12.8	7.7	6.6	3.3	2.4	2.9	14.4
8m	0.88	5.7	-	28.9	11.4	18.9	9.1	9.0	6.8	3.4	-	-	14.0
10m	0.56	2.5	-	22.2	5.0	15.9	5.2	9.7	5.4	2.7	-	-	12.4

Escape Route



Open Plan

