

IP 40	8Y Warranty	36m Viewing Distance	Wall Mounted
Class I	1.8 Kg	Ni-Mh Battery	6500K

Materials

Housing: Painted Steel
 Panel Legend: Polycarbonate

Standard Colour: White Ral 9016

Alternative Colour: Black - RAL 9017
 Add /BL to order code

Warranty

Standard Warranty: 8 Years
 Alternative Warranty: 10 Years
 Add /10Y to order code

Order Code	EXM3/LED/**/ST
Mode of operation	Maintained Self Test
Emergency duration	3 hours
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	7.2VA
Battery Type	Rechargeable Ni-Mh 3.6V, 2.1Ah
Battery low voltage cut off	3V
Battery discharge current @ 3.6Vdc	0.485A
Battery discharging limits	0.3-0.6A
Lamp	12 x High Powered White LEDs
Lamp Life	L ₈₀ B ₅₀ 80000 Hours
Nominal lamp current	I _{rated} = 0.35A
Nominal lamp power	P _{rated} = 1W
Degree of protection	IP40 - for indoor use only
Cable entry	Two 20mm conduit points on top of fitting, single 20mm conduit point on either side, and rear BESA terminal box mounting
Luminaire class	Class I
Weight	1.8kg
Packaging Weight	0.22kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
Self Test	EXM3/LED**ST	Maintained	3.6V 2.1Ah NiMh	70272	36m	430	201	60


Alternative Legends




Replace ** with 01 for application of Left Arrow
 PN: 01710



Replace ** with 02 for application of Down Arrow
 PN: 01733



Replace ** with 03 for application of Right Arrow
 PN: 01754



Replace ** with 04 for application of Up Arrow
 PN: 01775