

IP 40	8Y Warranty	36m Viewing Distance	Wall Mounted
Class I	 1.6 Kg	1W	6500K

Order Code	EX/LED/230S **
Mode of operation	Slave
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	6VA, I _{nom} = 0.025A
Lamp	12x Samsung White LED
Lamp Life	L ₈₀ B ₅₀ 80000 Hours
Nominal lamp current	I _{rated} = 0.35A
Nominal lamp power	P _{rated} = 1W
Degree of protection	IP40 - for indoor use only.
Cable entry	Two 20mm conduit points on top of fitting, single 20mm conduit point on either side, and rear BESA terminal box mounting
Luminaire class	Class I
Weight	1.6kg
Packaging Weight	0.161kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity.

Materials

Housing: Painted Steel
 Panel Legend: Polycarbonate
 Standard Colour: White Ral 9016
 Alternative Colour: Black - RAL 9017
 Add /BL to order code

Warranty

Standard Warranty: 8 Years
 Alternative Warranty: 10 Years
 Add /10Y to order code

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
Central Battery	EX/LED/230S **	Slave	n/a	n/a	36 Metres	430	201	60
Alternative Systems Available:								
Standalone	EXM3/LED **	Maintained	4.8V 1.3Ah NiMh	70229	36 Metres	430	201	60
DALI	EXM3/LED/**/DA	Maintained	3.6v 2.1Ah NiMh	70251	36 Metres	430	201	60
DALI Central Battery	ZEXLED230S**DA	Slave	n/a	n/a	36 Metres	430	201	60


Alternative Legends



Replace ** with 01 for application of Left Arrow
 PN: 01710



Replace ** with 02 for application of Down Arrow
 PN: 01733



Replace ** with 03 for application of Right Arrow
 PN: 01754



Replace ** with 04 for application of Up Arrow
 PN: 01775