


# Vanguard

## Wall Mounted (WK) Slave Exit



IP 40	8Y Warranty	Stainless Steel	Side Wall Mounted
32m Viewing Distance	2.75 Kg	Class I	

### Materials

Housing: Stainless Steel  
 Panel Legend: Acrylic

Standard Colour: Stainless Steel  
 Alternative Colours available upon request

### Warranty

Standard Warranty: 8 Years  
 Alternative Warranty: 10 Years  
 Add /10Y to order code

Order Code	ZVGDLED240SWK
Mode of Operation	Slave
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	5VA
Lamp	8 x High Powered White Samsung LEDs
Lamp Life	L <sub>80</sub> B <sub>50</sub> 80000 Hours
Nominal lamp current	I <sub>rated</sub> = 0.35A
Nominal lamp power	P <sub>rated</sub> = 1W
Ingress Protection	IP40
Cable entry	20mm Rear entry
Luminaire class	Class I
Weight	1.7 kg (no panel) 2.5 kg (c/w Panel fitted)
Packaging Weight	0.162 kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 55°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)					
						A	B	C	D	E	F
Central Battery	ZVGDLED240SWK	Slave	n/a	n/a	32 Metres	10	284	100	75	290	298
Alternative Systems Available:											
Standalone	VGDM3/LED/WK	Maintained	4.8V 1.3Ah NiMh	70229	32 Metres	10	284	100	75	290	298
DALI	ZVGD3LWKDALI	Maintained	3.6V 4Ah NiMh	70232	32 Metres	10	284	100	75	290	298

### Legends (Ordered Separately)



Left /Right Arrow (Left one side, Right opposite side)  
 PN: LPVGDIS13WKVL



Down Arrow (both sides)  
 PN: LPVGDWKIS2WKVL



Up Arrow (both sides)  
 PN: LPVGDWKIS2WKVL

**Additional options of Printed Panels available. Contact Ventilux for further details.**