


VAC 1200

4ft Anti-Corrosive LED Bulkhead



Applications

Car Parks

Food Processing

Industrial

Manufacturing

Warehouse

Features

Frosted
Diffuser

Flicker-Free
Driver

4000K

Wall &
Ceiling-
Mounting

Beam
Angle
118.9°

Class
I

IP
65

3Y
Warranty

Order Code	See below
Input voltage	230-240VAC
Lamp Wattage	See below
Power factor	0.9
Lamp colour	4000K
Lamp Lifetime	L ₈₀ B ₅₀ 47500Hrs
Beam Angle	118.9°
Ingress Protection	IP65
Impact Resistance	IK08
Cable entry	20mm on Ends and rear of product
Luminaire class	Class I
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22, EN 55015
Environment	0°C to 45°C up to 80% relative humidity

Materials

Housing:

Polycarbonate

Geartray:

Painted steel

Fixing Clips:

Stainless steel

Standard Colour:

Grey (Base)

Warranty

Standard Warranty:

3 Years

System	Order Code	Mode of Operation	Battery	Battery P/N	Wattage	Lumens (mains)	Lumens (Emergency)	Power Consumption	Luminaire efficacy	Dimensions (mm)		
										A	B	C
Mains	VAC12/21W/230	Mains	n/a	n/a	21W	3212	n/a	25.2 VA	152.9 lm/W	1240	100	84
Mains	VAC12/27W/230	Mains	n/a	n/a	27W	4039	n/a	32.4 VA	149.5 lm/W	1240	100	84
Mains	VAC12/32W/230	Mains	n/a	n/a	32W	4918	n/a	38.4 VA	153.6 lm/W	1240	100	84
Mains	VAC12/37W/230	Mains	n/a	n/a	37W	5624	n/a	44.4 VA	152.0 lm/W	1240	100	84
Standalone	VAC12/M3/21W	Maintained	4.8V 4.5Ah NiCad	70123	21W	3212	612	31.7 VA	152.9 lm/W	1240	100	84
Standalone	VAC12/M3/27W	Maintained	4.8V 4.5Ah NiCad	70123	27W	4039	598	38.9 VA	149.5 lm/W	1240	100	84
Standalone	VAC12/M3/32W	Maintained	4.8V 4.5Ah NiCad	70123	32W	4918	614	44.9 VA	153.6 lm/W	1240	100	84
Standalone	VAC12/M3/37W	Maintained	4.8V 4.5Ah NiCad	70123	37W	5624	608	50.9 VA	152.0 lm/W	1240	100	84

Please note- For DALI emergency options see our VAC PRO range

