


VAC 1200

4ft Anti-Corrosive LED Bulkhead



Applications

- Car Parks
- Food Processing
- Industrial
- Manufacturing
- Warehouse

Features

- Frosted Diffuser
- Flicker-Free Driver
- 4000K
- Wall & Ceiling-Mounting
- Beam Angle 118.9°
- Class I
- IP 65
- 8Y Warranty

Order Code	See below
Input voltage	230-240VAC
Lamp Wattage	See below
Power factor	0.9
Lamp colour	4000K
Lamp Lifetime	L ₈₀ B ₅₀ 127000Hrs
Beam Angle	118.9°
Ingress Protection	IP65
Impact Resistance	IK10
Cable entry	20mm on Ends and rear of product
Luminaire class	Class I
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22, EN 55015
Environment (Mains)	-20°C to 55°C up to 80% relative humidity
Environment (Emergency)	0°C to 45°C up to 80% relative humidity

Materials

Housing: Polycarbonate
 Geartray: Painted steel
 Fixing Clips: Stainless steel
 Mounting Kit: Stainless steel

Standard Colour: Grey (Base)

Warranty

Standard Warranty: 8 Years
 Alternative Warranty: 10 Years
 Add **/10Y** to order code

Also Available With:

DALI Mains
 Central Battery Systems
 Movement Sensors
 CASAMBI

System	Order Code	Mode of Operation	Battery	Battery P/N	Wattage	Power Consumption	Lumens (mains)	Lumens (Emergency)	Luminaire efficacy	Dimensions (mm)		
										A	B	C
Mains	VAC12/21W/230	Mains	n/a	n/a	21W	24.3	3212	N/A	152.9 lm/W	1240	100	84
Mains	VAC12/27W/230	Mains	n/a	n/a	27W	29.1	4039	N/A	149.5 lm/W	1240	100	84
Mains	VAC12/32W/230	Mains	n/a	n/a	32W	34.5	4918	N/A	153.6 lm/W	1240	100	84
Mains	VAC12/37W/230	Mains	n/a	n/a	37W	39.2	5624	N/A	152.0 lm/W	1240	100	84
Standalone	VAC12M3/LED/21W	Maintained	4.8V 4.5Ah Ni-Cad	70123	21W	31.3	3212	610	152.9 lm/W	1240	100	84
Standalone	VAC12M3/LED/27W	Maintained	4.8V 4.5Ah Ni-Cad	70123	27W	36.1	4039	610	149.5 lm/W	1240	100	84
Standalone	VAC12M3/LED/32W	Maintained	4.8V 4.5Ah Ni-Cad	70123	32W	41.5	4918	610	153.6 lm/W	1240	100	84
Standalone	VAC12M3/LED/37W	Maintained	4.8V 4.5Ah Ni-Cad	70123	37W	46.2	5624	610	152.0 lm/W	1240	100	84
DALI	VAC12M3/LED/21W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	21W	31.3	3212	882	152.9 lm/W	1240	100	84
DALI	VAC12M3/LED/27W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	27W	36.1	4039	882	149.5 lm/W	1240	100	84
DALI	VAC12M3/LED/32W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	32W	41.5	4918	882	153.6 lm/W	1240	100	84
DALI	VAC12M3/LED/37W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	37W	46.2	5624	882	152.0 lm/W	1240	100	84
DALI Wireless	VAC12M3/LED/21W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	21W	31.3	3212	882	152.9 lm/W	1240	100	84
DALI Wireless	VAC12M3/LED/27W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	27W	36.1	4039	882	149.5 lm/W	1240	100	84
DALI Wireless	VAC12M3/LED/32W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	32W	41.5	4918	882	153.6 lm/W	1240	100	84
DALI Wireless	VAC12M3/LED/37W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	37W	46.2	5624	882	152.0 lm/W	1240	100	84