


VAC 1500

5ft Anti-Corrosive LED Bulkhead



Applications

Car Parks

Food Processing

Industrial

Manufacturing

Warehouse

Features

Frosted
Diffuser

Flicker-Free
Driver

4000K

Wall &
Ceiling-
Mounting

Beam
Angle
118.9°

Class
I

IP
65

3Y
Warranty

Order Code	See below
Input voltage	230-240VAC
Lamp	44W as Standard- selectable for 30,37,52W
Power consumption	52.8VA
Power factor	0.9
Lamp colour	4000K
Lamp Lifetime	L ₈₀ B ₅₀ 47500Hrs
Beam Angle	118.9°
Ingress Protection	IP65
Impact Resistance	IK08
Cable entry	20mm on Ends and rear of product
Luminaire class	Class I
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22, EN 55015
Environment	0°C to 45°C up to 80% relative humidity

Materials

Housing: Polycarbonate
Geartray: Painted steel
Fixing Clips: Stainless steel
Standard Colour: Grey (Base)

Warranty

Standard Warranty: 3 Years

System	Order Code	Mode of Operation	Battery	Battery P/N	Lumens	Luminaire efficacy	Dimensions (mm)		
							A	B	C
Mains	VAC15/30W/230	Mains	N/A	N/A	4461	148.7 lm/W	1540	100	84
Standalone	VAC15/M3/30W	Maintained	4.8V 4.5Ah NiCad	70123	4461 (595 emergency)	148.7 lm/W	1540	100	84
Mains	VAC15/37W/230	Mains	N/A	N/A	5442	147.1 lm/W	1540	100	84
Standalone	VAC15/M3/37W	Maintained	4.8V 4.5Ah NiCad	70123	5442 (588 emergency)	147.1 lm/W	1540	100	84
Mains	VAC15/44W/230	Mains	N/A	N/A	6570	149.3 lm/W	1540	100	84
Standalone	VAC15/M3/44W	Maintained	4.8V 4.5Ah NiCad	70123	6570 (597 emergency)	149.3 lm/W	1540	100	84
Mains	VAC15/52W/230	Mains	N/A	N/A	7582	145.8 lm/W	1540	100	84
Standalone	VAC15/M3/52W	Maintained	4.8V 4.5Ah NiCad	70123	7582 (583 emergency)	145.8 lm/W	1540	100	84

Please note- For DALI emergency options see our VAC PRO range

Photometrics

