


VAC 1500


5ft Anti-Corrosive LED Bulkhead



Applications



Features



Order Code	See below
Input voltage	230-240VAC
Power factor	0.9
Lamp colour	4000K
Lamp Lifetime	L ₈₀ B ₅₀ 127000Hrs
Beam Angle	118.9°
Ingress Protection	IP65
Impact Resistance	IK10
Cable entry	20mm on Ends and rear of product
Luminaire class	Class I
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22, EN 55015
Environment (Mains)	-20°C to 55°C up to 80% relative humidity
Environment (Emergency)	0°C to 45°C up to 80% relative humidity

Materials

Housing: Polycarbonate
 Geartray: Painted steel
 Fixing Clips: Stainless steel
 Mounting Kit: Stainless steel

Standard Colour: Grey (Base)

Warranty

Standard Warranty: 8 Years
 Alternative Warranty: 10 Years
 Add /10Y to order code

Also Available With:

DALI Mains
 Central Battery Systems
 Movement Sensors
 CASAMBI

System	Order Code	Mode of Operation	Battery	Battery P/N	Wattage	Power Consumption	Lumens (mains)	Lumens (Emergency)	Luminaire efficacy	Dimensions (mm)		
										A	B	C
Mains	VAC15/30W/230	Mains	n/a	n/a	30W	33.9	4461	N/A	148.7 lm/W	1540	100	84
Mains	VAC15/37W/230	Mains	n/a	n/a	37W	40.1	5442	N/A	147 lm/W	1540	100	84
Mains	VAC15/44W/230	Mains	n/a	n/a	44W	47.4	6570	N/A	149.3 lm/W	1540	100	84
Mains	VAC15/51W/230	Mains	n/a	n/a	51W	54.6	7582	N/A	151.6 lm/W	1540	100	84
Standalone	VAC15M3/LED/30W	Maintained	4.8V 4.5Ah Ni-Cad	70123	30W	40.9	4461	610	148.7 lm/W	1540	100	84
Standalone	VAC15M3/LED/37W	Maintained	4.8V 4.5Ah Ni-Cad	70123	37W	47.1	5442	610	147 lm/W	1540	100	84
Standalone	VAC15M3/LED/44W	Maintained	4.8V 4.5Ah Ni-Cad	70123	44W	54.4	6570	610	149.3 lm/W	1540	100	84
Standalone	VAC15M3/LED/51W	Maintained	4.8V 4.5Ah Ni-Cad	70123	51W	61.6	7582	610	151.6 lm/W	1540	100	84
DALI	VAC15M3/LED/30W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	30W	40.9	4461	882	148.7 lm/W	1540	100	84
DALI	VAC15M3/LED/37W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	37W	47.1	5442	882	147 lm/W	1540	100	84
DALI	VAC15M3/LED/44W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	44W	54.4	6570	882	149.3 lm/W	1540	100	84
DALI	VAC15M3/LED/51W/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	51W	61.6	7582	882	151.6 lm/W	1540	100	84
DALI Wireless	VAC15M3/LED/30W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	30W	40.9	4461	882	148.7 lm/W	1540	100	84
DALI Wireless	VAC15M3/LED/37W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	37W	47.1	5442	882	147 lm/W	1540	100	84
DALI Wireless	VAC15M3/LED/44W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	44W	54.4	6570	882	149.3 lm/W	1540	100	84
DALI Wireless	VAC15M3/LED/51W/DAW	Maintained	6.4V 6.4Ah LiFePO4	70258	51W	61.6	7582	882	151.6 lm/W	1540	100	84